

Swimming Pool Heat Pump Specification(R410A)-(115-120V/1/60HZ)

FOB Guangzhou(USD)-based on capillary, 16M power cable (AWG14) with USA plug		350
Model		SCH-SP55MA
Power supply		115-120V/1/60HZ
Heating:(Air27℃ ,Water27℃,Humidity80%)	Capacity(KW)	5.68
	Capacity(KBTU)	19.38
	power input(KW)	0.91
	power input(KBTU)	3.10
	COP	6.24
Fan Quqntity		1
water flow		m3/h ≅ 2.35
Refrigerant		R410A
Refrigerant weight		kg 0.85
Min pressure/max pressure(Mpa)		1.5/4.2
unit net dimensions(mm) L*W*H		900*365*556
Carton box sizes(mm) L*W*H		940*415*615
net weight		kg 40
gross weight		kg 46
noise at 1 m		dB(A) 47
noise at 1 0m		dB(A) 28
compressor brand		HITACHI、SANYO
water proof level		IPX4
REMARKS:		

The price valid will be based on the following conditions:

1. Exchange rate USD1: CNY6.60. 2.Copper standard price 45000RMB/ton. 3. Heating only, use capillary&with four way valve. 4. Including 16M power cable (AWG14) with USA plug. 5. 2018 price base on copper month average price at 50000RMB/TON, when last month average copper price \pm 5000RMB, our whole unit price will adjust \pm 3%. For example, when Fibropool place a order to DERON in February 2018, the month average copper price of January 2018 was 45000RMB/TON then we will deduct 3% price for you, if the the month average copper price of January 2018 was 55000RMB/TON then we will increase 3% price for you. Similar counting like this way. The copper(Cu) monthly average price will refer to SHMET(www.en.shmet.com). 6. the bonding lugs & Energy stickers offered by Fibropool directly, others are similar as First order.